

go-archetype



<https://go-archetype.dev/>

@rantav

#truestory



whoami?



The Challenge

Static project template

First attempt

Solution: Use a tool

Second attempt

Solution: use a tool. What tools are out there?

- Maven archetype
 - Still static (plus requires installing mvn)
- Rails generators
 - Too specific for RoR
- Yeoman
 - Frontend focused
- CRA - Create React App
 - Too specific for React

Solution: use a tool. OK, let's look for generic tools

- Python Cookiecutter <https://github.com/cookiecutter/cookiecutter>
 - Very nice.
 - Very flexible
 - Large community
 - Jinja2 for templating
 - Even path names are templates.
 - Plus you can write python scripts for hooks etc
- Example Go template: <https://github.com/lacion/cookiecutter-golang>



Solution: use a tool. Yet another generic tool

- Hygen <http://www.hygen.io/>
 - Written by my friend Dotan
 - Also very capable
 - Templating via jsx (like React)



hygen

The Problem

Name	Last commit
📁 .githooks	Add lint and pre
📁 _templates	Upgrage hygen
📁 admin	Add and improv
📁 cmd	Add tests for gr
📁 grpc	Add a sever tes
📁 internal/generated/go-template-grpc	Add gRPC and a
📁 service	Run a gRPC clie
📄 .gitignore	Ci cont
📄 .gitlab-ci.yml	Ci cont
📄 Makefile	Upgrage hygen

Templates

Code

📁 grpc

📄 .00cleaner.t

📄 .gitlab-ci.yml.t

📄 Makefile.t

📄 README.md.t

📄 go.mod.t

📄 main.go.t

📄 main.go.t 113 Bytes 🔗

```
1  ---
2  to: main.go
3  ---
4  package main
5
6  import (
7      "<%= repo_path %>/<%= name %>/cmd"
8  )
9
10 func main() {
11     cmd.Execute()
12 }
```



WHAT DO WE WANT?



**WRITE IN OUR
NATIVE LANGUAGE**



WHAT MORE DO WE WANT?



DRY



go-archetype

The Solution

```
→ af-go-template git:(master) .tools/bin/go-archetype-0.1.11/go-archetype transform --transformations transformations.yml --source=. --destination .tmp/go/my-go-project
```



```
func createCmd(log logger.Logger) *cobra.Command {
    var (
        cmd = &cobra.Command{
            Use:     "test-client",
            Short:  "Test the gRPC or HTTP client, connect",
            Long:   `First run the server using the "serve"
Then run this test-client command to connect to this serv
        }
        // BEGIN __INCLUDE_GRPC__
        grpcServerAddress = cmd.Flags().String("grpc-serv
            "Network address of the gRPC server. Could us
        // END __INCLUDE_GRPC__
        // BEGIN __INCLUDE_HTTP__
        httpServerAddress = cmd.Flags().String("http-serv
            "Network address of the HTTP server.")
        // END __INCLUDE_HTTP__
    )
}
```

Markers

Markers

transformations.yml

```
- name: include grpc - parts of files
  type: include
  region_marker: __INCLUDE_GRPC__
  condition: .include_grpc
  files: ["Makefile", "**/*.go", "deployments/*"]
- name: include tracing - parts of files
  type: include
  region_marker: __INCLUDE_TRACING__
  condition: .include_tracing
  files: ["**/*.go", "deployments/*"]
- name: include http - parts of files
  type: include
  region marker:    INCLUDE HTTP
```

User inputs

```
inputs:
  - id: name
    text: What is the project name? (e.g. my-awesome-go-project)
    type: text
  - id: repo_path
    text: What is the project repo path, without the project name?
    type: text
  - id: description
    text: What is a long project description? (long texts are allowed)
    type: text
  - id: include_grpc
    text: Should gRPC functionality be included?
    type: yesno
  - id: include_tracing
    text: Should Jaeger tracing functionality be included?
    type: yesno
```

User inputs

```
inputs:
  - id: name
    text: What is the project name? (e.g. my-awesome-go-project)
    type: text
  - id: repo_path
    text: What is the project repo path, without the project name?
    type: text
  - id: description
    text: What is a long project description? (long texts are OK)
```

```
→ af-go-template git:(master) .tools/bin/go-archetype-0.1.11/go-archetype transform --transformations transformations.yml
-destination .tmp/go/my-go-project
? What is the project name? (e.g. my-awesome-go-project) hello-go
? What is the project repo path, without the project name? (e.g. gitlab.appsflyer.com/rta) gitlab.appsflyer.com/rantav
? What is a long project description? (long texts are OK, but no newlines) This is just a test project
? Should gRPC functionality be included? (y/N) █
```

```
id: include_gracing
text: Should Jaeger tracing functionality be included?
type: yesno
```

Search and replace. But with a twist

```
- name: project description
  type: replace
  pattern: A template project
  replacement: "{{ wrap 80 .description }}"
  files: ["cmd/server/main.go", "README.md"]
- name: project path
  type: replace
  pattern: gitlab.appsflyer.com/go/af-go-template ← Pattern to search
  replacement: "{{ .repo_path }}/{{ .name }}" ← Replace with this
  files: ["*.go", "**/*.go", "go.mod", "go.sum", "Makefile"]
- name: project name
  type: replace
  pattern: af-go-template
  replacement: "{{ .name }}"
  files: ["*.go", "**/*.go", "**/*.sh", ".gitignore", "README.md"]
- name: project name in gRPC
```

Search and replace. But with a twist

```
- name: project description
  type: replace
  pattern: A template project
  replacement: |"{{ wrap 80 .description }}"|
  files: ["cmd/server/math.go", "README.md"]
- name: project path
  type: replace
  pattern: gitlab.appsflyer.com/go/af-go-template
  replacement: |"{{ .repo_path }}/{{ .name }}"|
  files: ["*.go", "**/*.go", "go.mod", "go.sum", "Makefile"]
- name: project name
  type: replace
  pattern: af-go-template
  replacement: "{{ .name }}"
  files: ["*.go", "**/*.go", "**/*.sh", ".gitignore", "README.md"]
- name: project name in gRPC
```

Usage, Tips and Tricks

Tips and Tricks - Go templates

```
- name: project path  
  type: replace  
  pattern: gitlab.appsflyer.com/go/af-go-template  
  replacement: "{{ .repo_path }}/{{ .name }}"
```

```
- name: project description  
  type: replace  
  pattern: A template project  
  replacement: "{{ wrap 80 .description }}"
```

Tips and Tricks - Go templates

```
- name: project name in gRPC proto
  type: replace
  pattern: af_go_template
  replacement: "{{ .name | snakecase }}"
```

```
- name: build with protoc or not
  type: replace
  pattern: "build: protoc"
  replacement: "{{ if .include_grpc }}build: protoc{{ else }}build:{{end}}"
```

Tips and Tricks - the sprig library functions

- All Sprig library functions are available.
- Examples:
 - `trim`
 - `upper`
 - `lower`
 - `title`
 - `wrap`
 - `plural`
 - `snakecase`
 - `camelcase`
 - `kebabcase`

Tips and Tricks - Global ignore list (like .gitignore)

```
1 transformations.yml
ignore:
  - .git/
  - transformations.yml
  - CHANGELOG.md
  - .tmp/
  - .gopath/
  - pkg/grpc/lib
  - .testCoverage.txt
  - scripts/init.sh
```

Tips and Tricks - Global before and after scripts

before:

operations:

- sh:

- echo "Starting to generate proje

after:

operations:

- sh:

- cd {{.destination}} && goimports -w .

- cd {{.destination}} && gofmt -s -w .

- cd {{.destination}} && make build

- cd {{.destination}} && make tidy

Tips and Tricks - Injected variables

- All user inputs are injected to the `before` and `after` operations as well as all other templates
 - E.g. `{{ .include_grpc }}` // <- this is user input (bool)
- As well as some meta variables
 - `{{ .source }}`
 - `{{ .destination }}`

Tips and Tricks - Include/exclude entire dirs or files

transformations:

- name: include grpc - whole files

type: include

region_marker: *When region marker is empty*

condition: .include_grpc

files: ["pkg/grpc/**", "pkg/admin/grpc*"]

Tips and Tricks - Include/exclude sections inside files

```
- name: include tracing - parts of files
  type: include
  region_marker: __INCLUDE_TRACING__
  condition: .include_tracing
  files: ["**/*.go", "deployments/*"]
```

```
// BEGIN __INCLUDE_TRACING__
c.TracingProbability,
c.JaegerHost,
// END __INCLUDE_TRACING__
```

Example: Not just .go files. A Makefile

```
# BEGIN __INCLUDE_GRPC__
## protoc: run the protoc compiler
protoc: $(PROTOC_BIN) protoc-gen-go
        mkdir -p pkg/grpc/lib
        $(PROTOC_BIN) --proto_path=pkg/grpc/idl/ --go_out
# END __INCLUDE_GRPC__
```

Summary

- go-archetype lets you easily create blueprints
 - Single code base in your native language (Go, Python, JS, Clojure)
 - Using comments as markers
 - And a single transformations.yml file
- User inputs
 - String (e.g. project_name)
 - Boolean (e.g. include_grpc)
- Transformations
 - Include/exclude entire file
 - Include/exclude parts of files (using inline code comments)
- Search and Replace
 - With the power of go text templates (`{{ .name | snakecase }}`)

<https://go-archetype.dev/>

Visit and star my project 🙏